FIBRESYSTEMS

Advert specifications for print

Overall metric page size 213mm wide x 282mm deep

Page unit	*Live	Trim	Bleed
Full page	189w x 258	-	-
Full page (Bleed)	189w x 258	213w x 282h	219w x 288h
Double page spread	402w x 258h	-	-
Double page spread (Bleed)	402w x 258h	426w x 282h	432w x 288h
1/2 page vertical	92w x 258h	-	-
1/2 page vertical (Bleed)	92w x 258h	104w x 282h	107w x 288h
1/2 page horizontal	189w x 129h	-	-
1/2 page horizontal (Bleed)	189w x 129h	213w x 141h	219w x 144h
1/4 page	92w x 129h	-	-
1/4 page strip (Bleed)	43w x 258h	55w x 282h	58w x 288h
1/3 page vertical	59w x 258h	-	-
1/3 page vertical (Bleed)	59w x 258h	71w x 282h	74w x 288h
1/3 page horizontal	189w x 85h	-	-

Bleed: These are the dimensions to use if graphics are to print beyond the edge of the final printed page.

Trim: These dimensions are where the page will be cut and represents the final dimensions of the printed magazine.

*Live: This is the area where text and graphics can be placed that is a safe distance from the trim size. these dimensions will prevent the loss of text or graphics when the page is trimmed. This measurement is a recommendation only.

All measurments are in mm

Full page requirements

- - - - - Bleed 219(w)mm x 288(h)mm
—— Trim 213(w)mm x 282(h)mm
—— Live 200(w)mm x 270(h)mm

Double page spread requirements

- - - - - Bleed 432(w)mm x 288(h)mm
—— Trim 426(w)mm x 282(h)mm
—— Live 410(w)mm x 270(h)mm

Belly wrap requirements

Outside Back Outside Front

Inside Front Inside Back

- - - - - Bleed 3mm (all the way around)
—— Width (each 'page') 150mm
—— Height 100mm

Digital file requirements
PDF-X1a, PDF, EPS and Tiff files are accepted.
All high resolution images and fonts must be embedded in files. Images must be 300dpi/CMYK